


Accesorios PE Inyectado para Tuberías PE-100

TARIFA PVP A-Presión




BRIDA LOCA ACERO BICROMATADO NORMALIZADA SEGÚN NORMAS DIN

| Medida Brida DN | Medida PE (mm) | DIN 2576 PN 10 | | DIN 2502 PN16 | | DIN 2503 PN 25 | |
|-----------------------|----------------|----------------|-------------|---------------|---------------|----------------|---------------|
| | | k | Código | k | Código | k | Código |
| 40 | 50 | • 110 | 1 34 91 050 | 110 | • 1 34 91 050 | 110 | * 1 34 92 050 |
| 50 | 63 | • 125 | 1 34 91 063 | 125 | • 1 34 91 063 | 125 | * 1 34 92 063 |
| 65 | 75 | • 145 | 1 34 91 075 | 145 | • 1 34 91 075 | 145 | * 1 34 92 075 |
| 80 | 90 | • 160 | 1 34 91 090 | 160 | • 1 34 91 090 | 160 | * 1 34 92 090 |
| 100 | 110 | • 180 | 1 34 91 110 | 180 | • 1 34 91 110 | 190 | * 1 34 92 110 |
| 100 | 125 | • 180 | 1 34 91 111 | 180 | • 1 34 91 111 | 190 | * 1 34 92 111 |
| 125 | 125 | • 210 | 1 34 91 125 | 210 | • 1 34 91 125 | 220 | * 1 34 92 125 |
| 125 | 140 | • 210 | 1 34 91 140 | 210 | • 1 34 91 140 | 220 | * 1 34 92 140 |
| 150 | 160 | • 240 | 1 34 91 160 | 240 | • 1 34 91 160 | 250 | * 1 34 92 160 |
| 150 | 180 | • 240 | 1 34 91 180 | 240 | • 1 34 91 180 | 250 | * 1 34 92 180 |
| 200 | 200 | • 295 | 1 34 90 200 | 295 | • 1 34 91 200 | 310 | * 1 34 92 200 |
| 200 | 225 | □ 295 | 1 34 90 225 | 295 | □ 1 34 91 225 | 310 | * 1 34 92 225 |
| 250 | 250 | • 350 | 1 34 90 250 | 355 | • 1 34 91 250 | 370 | * 1 34 92 250 |
| 250 | 280 | □ 350 | 1 34 90 280 | 355 | □ 1 34 91 280 | 370 | * 1 34 92 280 |
| 300 | 315 | • 400 | 1 34 90 315 | 410 | • 1 34 91 315 | 430 | * 1 34 92 315 |
| 350 | 355 | • 460 | 1 34 90 355 | 470 | • 1 34 91 355 | 490 | * 1 34 92 355 |
| 400 | 400 | • 515 | 1 34 90 400 | 525 | • 1 34 91 400 | 550 | * 1 34 92 400 |
| 500 | 450 | □ 525 | 1 34 90 450 | 585 | □ 1 34 91 450 | - | - |
| 500 | 500 | • 620 | 1 34 90 500 | 650 | □ 1 34 91 500 | - | - |
| 600 | 560 | □ 725 | 1 34 90 560 | 770 | • 1 34 91 560 | - | - |
| 600 | 630 | • 725 | 1 34 90 630 | 770 | • 1 34 91 630 | - | - |
| 800 | 800 | □ 950 | 1 34 90 800 | - | □ 1 34 91 800 | - | - |



BRIDA ACERO ZINCADO SERIE LIGERA TALADRO SEGÚN NORMAS DIN

| Medida Brida DN | Medida PE (mm) | b (mm) | DIN 2576 PN 10 | | DIN 2502 PN16 | |
|-----------------------|----------------|--------|----------------|---------------|---------------|---------------|
| | | | k | Código | k | Código |
| 50 | 63 | 12 | 125 | • 1 34 98 063 | 125 | • 1 34 98 063 |
| 65 | 75 | 12 | 145 | • 1 34 98 075 | 145 | • 1 34 98 075 |
| 80 | 90 | 12 | 160 | • 1 34 98 090 | 160 | • 1 34 98 090 |
| 100 | 110 | 12 | 180 | • 1 34 98 110 | 180 | • 1 34 98 110 |
| 125 | 125 | 12 | 210 | • 1 34 98 125 | 210 | • 1 34 98 125 |
| 125 | 140 | 12 | 210 | • 1 34 98 140 | 210 | • 1 34 98 140 |
| 150 | 160 | 12 | 240 | • 1 34 98 160 | 240 | • 1 34 98 160 |
| 200 | 200 | 14 | 295 | • 1 34 97 200 | 295 | □ 1 34 98 200 |
| 250 | 250 | 14 | 350 | • 1 34 97 250 | 355 | □ 1 34 98 250 |
| 315 | 315 | 14,5 | 400 | • 1 34 97 315 | 410 | □ 1 34 98 315 |



BRIDA LOCA ALMA DE ACERO RECUBIERTA EN PP

| Medida Brida DN | Medida PE (mm) | Dimensiones (mm) | | | PN10 | PN16 |
|-----------------|----------------|------------------|----|-----|---------------|---------------|
| | | k | h | di | Código | Código |
| 40 | 50 | 110 | 18 | 62 | • 1 34 94 050 | • 1 34 94 050 |
| 50 | 63 | 125 | 18 | 78 | • 1 34 94 063 | • 1 34 94 063 |
| 65 | 75 | 145 | 18 | 92 | • 1 34 94 075 | • 1 34 94 075 |
| 80 | 90 | 160 | 20 | 108 | • 1 34 94 090 | • 1 34 94 090 |
| 100 | 110 | 180 | 20 | 128 | • 1 34 94 110 | • 1 34 94 110 |
| 100 | 125 | 180 | 20 | 135 | • 1 34 94 111 | • 1 34 94 111 |
| 125 | 125 | 210 | 24 | 158 | • 1 34 94 125 | • 1 34 94 125 |
| 125 | 140 | 210 | 24 | 158 | • 1 34 94 140 | • 1 34 94 140 |
| 150 | 160 | 240 | 24 | 178 | • 1 34 94 160 | • 1 34 94 160 |
| 150 | 180 | 240 | 24 | 188 | • 1 34 94 180 | • 1 34 94 180 |
| 200 | 200 | 295 | 26 | 235 | • 1 34 93 200 | • 1 34 94 200 |
| 200 | 225 | 295 | 26 | 238 | • 1 34 93 225 | □ 1 34 94 225 |
| 250 | 250 | 350 | 29 | 288 | • 1 34 93 250 | • 1 34 94 250 |
| 300 | 315 | 400 | 33 | 338 | □ 1 34 93 315 | • 1 34 94 315 |

Disponibilidad: ● Stock, □ 5-6 días, * Consultar